



Florida Water Blast, Inc.

12995 Automobile Blvd. Clearwater, FL 33762 - Wk. # 1-800-966-0614
E-Mail Address: floridawb@aol.com - Web Address: www.floridawaterblast.net

CMAFU- 2 Solids Filtration

Standard Features:

- Stainless steel construction
- Automatic filter media advance
- Used filter media collection tray - optional
- Cascade electrical eliminates excess input water
- Casters provide mobility and increased flexibility

Electrical: Power & Controls

STD- 120 Volt, 1 Phase, With GFCI

Finish Options

STD- CMAFU-2 Wheel Kit, Casters
OPT- Stand, CMAFU-2

System Covers

OPT- Top W/ Window, 19800-1 Tank, CMAFU-2
OPT- Cover, CMAFU-2 Waste Catch Container

Discharge Options

STD- Overflow To Drain, Gravity, For CMAFU-2
OPT- Output Conveyor CMAFU-2, W/ Stand, 8'
OPT- Auto Discharge To Sewer/ Tank For CMAFU-2

Inlet Options

STD- Single Inlet Feed, CMAFU-2
OPT- Inlet Pump Assembly CMAFU, 1/3 HP, Cast Iron
OPT- Inlet Pump Assembly CMAFU-2, 1/3 HP, Stainless Steel

Inlet Options, Second Pump

OPT- Dual Inlet Feed, CMAFU-2
OPT- Inlet Pump, Dual Inlet, 1/3HP, Stainless Steel
OPT- Inlet Pump, Dual Inlet, 1/4HP, Auto Sense

Inlet Accessories

OPT- Basket, Sump Pump Stand, To 0.5HP
OPT- Tank, Sump, 18" X 16" X 14

Specifications

Dimension: 51" L X 25" W X 28" H Weight: 182 LBS.

How CMAFU-2 System Works:

As dirty water is transferred to the CMAFU-2 wastewater passes through a bed of filter paper. As solids collected blind the filter paper, the water level rises on top of the paper. This engages a mechanical float activates the media advance motor and allows for a small amount of clean filter media to advance. The water level drops and media stops advancing. A single 100-yard roll of filter media allows for a tremendous amount of solids to be filtered without operator intervention. This will reduce the REPLACEMENT OF CARTRIDGE FILTERS & help keep the dirt out of your system.



[For Mor Information On Filtration Equipment Selection](#)